N A D I S

D E S I G N

TECHNICAL INFORMATION — Color Body Porcelain - Rectified

MODEL	**TIFFANY**	
COLOR	**WHITE / BEIGE / GRAY / GRAPHITE**	(Color does not affect test results)
REAL SIZE	**298 x 598 mm**	
FINISH	**SILK / NATURAL / ANTISLIP AS**	(For the different finishes see the test results)
THICKNESS	**9,6 mm**	

UNE-EN 1441:2016
DRY-PRESSED CERAMIC TILE - UNGLAZED (UGL) - WATER ABSORPTION INFERIOR THAN 0.5% - Group Bla - Annex G

STANDARD	ESSAY / FEATURES	REQUIRED	RESULT (*)
EN-ISO 10545 / 3	Water absorption	E ≤ 0,5%	E ≤ 0,3%
EN-ISO 10545 / 4	Bending strength	≥ 35 N/mm^2	> 40 N/mm^2
	Breaking strength	≥ 1300 N	> 2000 N
EN-ISO 10545 / 6	Resistance to deep abrasion	175 mm^3	Complies
EN-ISO 10545 / 11	Determination of crazing resistance	Required	Complies
EN-ISO 10545 / 12	Determination of frost resistance	Required	Complies
EN-ISO 10545 / 13	Resistance to chemical and swimming pool salts	Min UG/ UGL - B	UG / UGL - A
EN-ISO 10545 / 14	Determination of resistance to stain	Min. Class 3	Class 5
UNE ENV 12633	Slip resistance (Pendulum test)	Min. Class 1	**SILK** 1 **NATURAL** 1 **ANTISLIP AS** 3
DIN 51130	Critical angle (Inclined platform test)	Min. R9	**SILK** -- **NATURAL** R9 **ANTISLIP AS** R11
DIN 51097	Critical angle (Wet loaded barefoot test)	Min. Clase A	**SILK** -- **NATURAL** A **ANTISLIP AS** A+B+C
UNE EN 13501 - 1:2002	Reaction to fire		A1 / A1FL
UNE EN 14021 - 1:2002	Ecolabel and environmental statement		31 %

(*) The declared values are the average obtained in the internal laboratory of different productions. (march 2021)

31 %

ES19/85847

NADIS DESIGN S.L.
T: +34 964 89 13 89 - www.nadisdesign.com - info@nadisdesign.com