

# N A D I S

D E S I G N

## TECHNICAL INFORMATION

Color Body Porcelain - Rectified

MODEL	<b>MONDO</b>		
COLOR	<b>LIGHT / GRAY / DARK GRAY</b>	(Color does not affect test results)	
REAL SIZE	<b>1198 x 2600 mm</b>		
FINISH	<b>NATURAL</b>		
THICKNESS	<b>5,6 mm</b>		

### UNE-EN 1441:2016

DRY-PRESSED CERAMIC TILE - UNGLAZED (UGL) - WATER ABSORPTION INFERIOR THAN 0.5% - Group Bla - Annex G

STANDARD	ESSAY / FEATURES	REQUIRED	RESULT (*)
EN-ISO 10545 / 3	Water absorption	$E \leq 0,5\%$	$E \leq 0,3\%$
EN-ISO 10545 / 4	Bending strength	$\geq 35 \text{ N/mm}^2$	$> 40 \text{ N/mm}^2$
	Breaking strength	$\geq 700 \text{ N}$	$> 1000 \text{ N}$
EN-ISO 10545 / 6	Resistance to deep abrasion	$175 \text{ mm}^3$	Complies
EN-ISO 10545 / 11	Determination of crazing resistance	Required	Complies
EN-ISO 10545 / 12	Determination of frost resistance	Required	Complies
EN-ISO 10545 / 13	Resistance to chemical and swimming pool salts	Min UG/ UGL - B	UG / UGL - A
EN-ISO 10545 / 14	Determination of resistance to stain	Min. Class 3	Class 5
UNE EN 13501 - 1:2002	Reaction to fire		A1 / A1FL
UNE EN 14021 - 1:2002	Ecolabel and environmental statement		23 %

(\*) The declared values are the average obtained in the internal laboratory of different productions. (march 2021)



23 %



ES19/85847