

NADIS

D E S I G N

TECHNICAL INFORMATION

White Body – Rectified

MODEL	ARCTIC
COLOR	WHITE
REAL SIZE	298 x 898 mm
FINISH	MATT / SHINE (Finishes does not affect test results)
THICKNESS	10,6 mm

UNE-EN 1441:2016

DRY-PRESSED CERAMIC TILE - GLAZED (GL) - WATER ABSORPTION SUPERIOR THAN 10 % -- Group BIII – Annex L

STANDARD	ESSAY / FEATURES	REQUIRED	RESULT (*)
EN-ISO 10545 / 3	Water absorption	E > 10%	12% < E < 18%
EN-ISO 10545 / 4	Bending strength	≥ 12 N/mm ²	> 14 N/mm ²
	Breaking strength	≥ 600 N	> 650 N
EN-ISO 10545 / 12	Determination of frost resistance	Required	Complies
EN-ISO 10545 / 14	Determination of resistance to stain	Min. Class 3	Class 5
UNE EN 13501 - 1:2002	Reaction to fire		A1 / A1FL
UNE EN 14021 - 1:2002	Ecolabel and environmental statement		39 %

(*) The declared values are the average obtained in the internal laboratory of different productions. (march 2021)



39 %



ES19/85847

NADIS DESIGN S.L.

T: +34 964 89 13 89 - www.nadisdesign.com - info@nadisdesign.com