N A D I S

D E S I G N

TECHNICAL INFORMATION — Color Body Porcelain - Rectified

MODEL	**ALBOR**	
COLOR	**WHITE / CREAM**	(Color does not affect test results)
REAL SIZE	**1200 x 1200 mm**	
FINISH	**SILK / NATURAL HAMMERED / ANTISLIP AS**	(For the different finishes see the test results)
THICKNESS	**9 mm**	

UNE-EN 1441:2016

DRY-PRESSED CERAMIC TILE - GLAZED (GL) - WATER ABSORPTION INFERIOR THAN 0.5% - Group Bla - Annex G

STANDARD	ESSAY / FEATURES	REQUIRED	RESULT (*)
EN-ISO 10545 / 3	Water absorption	E ≤ 0,5%	E < 0,5%
EN-ISO 10545 / 4	Bending strength	≥ 35 N/mm^2	> 35 N/mm^2
	Breaking strength	≥ 1300 N	> 1300 N
EN-ISO 10545 / 6	Resistance to deep abrasion	175 mm^3	Complies
EN-ISO 10545 / 11	Determination of crazing resistance	Required	Complies
EN-ISO 10545 / 12	Determination of frost resistance	Required	Complies
EN-ISO 10545 / 13	Resistance to chemical and swimming pool salts	Min - B	B
EN-ISO 10545 / 14	Determination of resistance to stain	Min. Class 3	Class 5
UNE ENV 12633	Slip resistance (Pendulum test)	Min. Class 1	**NAT. HAMM.** 2 **ANTISLIP** 3
DIN 51130	Critical angle (Inclined platform test)	Min. R9	**NAT. HAMM.** R10 **ANTISLIP** R11
DIN 51097	Critical angle (Wet loaded barefoot test)	Min. Class A	**NAT. HAMM.** A+B **ANTISLIP** A+B+C
UNE EN 13501 - 1:2002	Reaction to fire		A1
EN -ISO 10545 / 7	Abrasion Resistance (PEI)		**WHITE** IV **CREAM** IV
VOC	Do not release volatile elements		
UNE EN 14021 - 1:2002	Ecolabel and environmental statement		45%

(*) The declared values are the average obtained in the internal laboratory of different productions. (January 2025)

45 %

ES19/85847

NADIS DESIGN S.L.
T: +34 964 89 13 89 - www.nadisdesign.com - info@nadisdesign.com