N A D I S

D E S I G N

TECHNICAL INFORMATION — Matt Porcelain – Straight Edge

MODEL	**CRATT**
COLOR	**BROWN / TAUPE / SAND / CLAY / GRENADE / BUTTER / OLIVE / FOREST / GRAY / BLUE / BLACK / WHITE**
FORMAT	**116x116 mm**
FINISH	**MATT GLAZED**
THICKNESS	**8,5 mm**

UNE-EN 1441:2016
PRESSED CERAMIC TILE – GLAZED (GL) – WATER ABSORPTION LESS THAN 0.5% -- Bla Group

STANDARD	ESSAY / FEATURES	REQUIREMENTS	RESULTS (*)
EN-ISO 10545 / 3	Water absorption	E ≤ 0,5%	E ≤ 0,5%
EN-ISO 10545 / 4	Bending strength	≥ 35 N/mm^2	≥ 35 N/mm^2
	Breaking strenght	≥ 1300 N	> 1300 N
EN-ISO 10545 / 12	Determination of frost resistance	Required	Complies
UNE EN ISO 10545-11	Determination of crazing resistance	Required	Complies
UNE EN 67-101	Scratch resistance Mohs	Min. 3	6
EN-ISO 10545 / 14	Determination of resistance to stain	Min. 1	5
UNE EN ISO 10545-13	Resistance to acids and bases at low concentrations	Min. LA	LA
UNE EN ISO 10545-13	Resistance to cleaning products	Min. A	A
EN 16165 – ANEXO C	Slip resistance (Pendulum Test)	Min. Class 1	2
EN 16165 – ANEXO B DIN 51130	Critical Angle of Sliding (Inclined Plataform)	Min. R9	R10
EN 16165 – ANEXO A DIN 51097	Critical Angle of Sliding (Wet Areas of Barefoot Walking)	Min. Class A	A+B
ANSI A326.3 – DCOF	Dynamic Coefficient of Friction		>0,42
UNE-EN ISO 10545-7 - PEI	Surface Abrasion Resistance		Class 3
VOC	Do not release volatile elements		
UNE EN 14021 - 1:2002	Ecolabel and environmental statement		39 %

(*) The values stated are the average obtained in our internal laboratory from different production runs. (September 2026)



39%



ES19/85847

NADIS DESIGN S.L.
T: +34 964 89 13 89 - www.nadisdesign.com - info@nadisdesign.com